

ANIMA

SCHEDA TECNICA

Revisione : 29/07/2025

Prodotto: **ANIMA**

Categoria: Linea Impero

Azienda: Loggia

General Characteristics

Glazing with a soft touch effect, formulated with special resins and fillers which give the product very special tactile and chromatic characteristics, allowing you to obtain decorated walls that are comfortable to the touch.

Application

For interior decorations.

Preparation



Before applying Anima it is necessary to adequately prepare the surface using powder or paste fillers (such as FLYSTUK), then smoothed with abrasive paper (a grit type P120 is recommended) after about 12 hours from the end of the application. After sanding, proceed with the elimination of dirt and dust, apply a coat of FISSACRIL acrylic fixative diluted with water in the ratio 1:1 / 1:3 and after 4-5 hours apply 2 coats of Universal Primer using a roller, spaced about 5-6 hours apart. The Universal Primer must be white or the same tone of color that was chosen for ANIMA.

Application Methods



Stainless steel trowel: after about 8 hours from the end of the Universal Primer application, proceed by spreading Anima ready-to-use using a stainless steel trowel with semicircular movements until the desired effect is created. Wait 4-6 hours and apply the second coat.

Roller: After about 8 hours from the end of applying Universal Primer, apply a coat of Anima diluted 5-10% with a fine-structure roller, avoiding creating overlaps.

Application temperature:	+5 ÷ +35	°C
Relative humidity of application:	< 85%	
Recommended thickness:	50 ÷ 100	µm per coat
Dust dry:	4 ÷ 6	h
Repaintable after:	12	h
Deep dry:	24	h
Tool cleaning:	water	

Painting:



The product can be colored with the tinting systems of the MAXXI line as well as with the universal colorants available on the market.

It is advisable to mix different manufacturing batches of the same color together to avoid possible differences in tone during application

Specific weight:	0,9 ÷ 1,0	Kg/l
pH:	7-8	
Solid in weight:	43%	
Theoretical yield:	12 – 13	mq/l per coat
Color	Card colors	
Appearance:	SOFT TOUCH	
Packs:	0,75 - 2,5- 4	l

Storage:



The unopened product, stored intact in a dry and cool place, has a shelf life of no less than 24 months.

After use, carefully close the package and store it upside down.



Minimum storage temperature: +5°C

Maximum storage temperature: +30°C

Safety Precautions:

For all information relating to the handling of the product, as well as its correct disposal, please refer to the Safety Data Sheet.

Warnings

The information contained in this sheet is provided to the best of our technical knowledge. However, these indications and suggestions cannot have the value of a guarantee for the applicator, since the conditions of use of the product are beyond our direct control. It is therefore advisable to ascertain the suitability of the product for the specific case with preliminary tests.

Loggia Industria Vernici S.r.l. Via Colle d'Alba di Levante – 04016 B.go S. Donato - Sabaudia (LT) –
ITALY

Tel. (+39) 0773 562212, Fax (+39) 0773 562034. www.loggia.it, E-mail commerciale@loggia.it.

BVQI certified company for the UNI EN ISO 9001-2000 quality system.